

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 July 2003 (10.07.2003)

PCT

(10) International Publication Number
WO 03/056576 A1

(51) International Patent Classification⁷: **H01B 7/28**, C08L 29/04, C08K 5/00, 5/09, C08L 31/04, 1101B 3/18, 3/44

(21) International Application Number: PCT/EP02/14554

(22) International Filing Date:
19 December 2002 (19.12.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
01130960.6 28 December 2001 (28.12.2001) EP
60/345,656 8 January 2002 (08.01.2002) US

(71) Applicant (for all designated States except US): **PIRELLI S.P.A** [IT/IT]; Viale Sarca, 222, I-20126 Milano (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **MARITANO, Mauro** [IT/IT]; Viale Molise 15, I-20052 Monza (IT). **DONETTI, Raffaella** [IT/IT]; Via 10 Martiri, 16, I-28074

Ghemme (IT). **CAMPANA, Antonio** [IT/IT]; Via Assietta, 9, I-20161 Milano (IT). **PAVAN, Massimiliano** [IT/IT]; Via degli Alpini, 9, I-24049 Verdello (IT). **SCORDAMAGLIA, Raimondo** [IT/IT]; Piazza Diocleziano, 2, I-20154 Milano (IT).


(74) Agent: **GIANNESI, Pier, Giovanni**; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, GR, GU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,

[Continued on next page]

(54) Title: WATER-RESISTANT TELECOMMUNICATION CABLE



(57) Abstract: Telecommunication cable comprising an elongated element housing at least one transmitting element, said elongated element comprising a water-soluble polymeric composition which comprises: - a vinyl alcohol/vinyl acetate (VA-VAc) copolymer having a saponification degree of from about 60% to about 95%; - a plasticizer; a hydrolysis stabilizer compound comprising a chelant group comprising two hydrogen atoms bonded to two respective heteroatoms selected from nitrogen, oxygen and sulfur, said two hydrogen atoms having a distance between each other of from 4.2×10^{-10} m to 5.8×10^{-10} m, preferably of from 4.5×10^{-10} m to 5.5×10^{-10} m, said stabilizer compound being present in an amount of at least 0.75 mmol per 100 g of VA-VAc copolymer. Said elongated element is in particular a buffer tube housing a plurality of optical fibers. The presence of the stabilizer allows to reduce the increase of the hydrolysis degree of the VA-VAc copolymer upon aging, thus maintaining the desired water blocking properties of the VA-VAc copolymer.

WO 03/056576 A1